



CLASS A AS/NZS 4233.1
PRESSURE CLEANER
NO RTO CERTIFICATION REQUIRED FOR OPERATORS

JETWAVE®

HIGH PRESSURE CLEANERS

Distributed by:

selmac
MILDURA

HORNET™ G2 4060 psi • 15 l/pm



Petrol Driven



Cold Water



Daily Usage

FIELDS OF APPLICATION

- Roof Cleaning
- Painting Contractors
- Cleaning Contractors
- Boat Yards and Ports
- Agricultural Equipment
- Councils & Government



JETWAVE
POWERED by
HONDA™



The Jetwave® Hornet G2™ revolutionises the single cylinder gearbox petrol driven cold water high pressure cleaner powered by HONDA™ Australian engineered and assembled; its innovation provides heavy duty users with a compact powerful, safe and easy to use unit that encompasses stainless steel exoskeleton (PEXO™) cover protection, centralised control & multi-configurable design.



HERO INNOVATIONS

- Stainless Steel Exoskeleton (PEXO™)**
Protective formed CNC cover to safeguard all components and for increased safety.
- Multi Configuration**
Industry first customisable modular build with precision heavy gauge steel chassis. Build it your way.
- Centralised Control**
Easily accessible one panel fascia mounted control(s) & components.
- AVPS™**
Anti-vibration protection system (AVPS™) for quieter & reliable performance.
- Versatile**
Multiple hose reel configurations.

STANDOUT FEATURES

- JW® Enhanced Italian triplex plunger pump** delivers performance and longer life.
- Low Speed professional pump** for increased reliability and longer maintenance intervals.
- Pull start HONDA™ GX390 Industrial Series OHV Engine.**
- Dual M22 screw hose coupling system.**
- Heavy duty washable inlet water filter.**
- Jetwave Safety System™ (JSS) thermal and safety valve** to prevent overheating in excessive bypass and over pressurisation.
- Integrated accessory storage** for gun and lance.
- Professional line accessories.**
- Quality pressure gauge.**
- Zero line pressure brass adjustable unloader valve.**
- Emergency Stop.**

Selmac Mildura

2160 Fifteenth Street, Irymple
VIC 3498

+61 3 5024 6005

admin@selmacmildura.com.au

www.selmacmildura.com.au

Compact - Modular frame design with top lift panels.

Protection - Designed for durability and a long life.

Control - Fascia mounted controls with plug n' go functionality.



Robust - Precision CNC frame.

Quality - Industry proven 'Italian' pump.

Power - Industrial OHV HONDA™ GX390 engine.

Flexibility - Multi configurable compact frame.

STANDARD EQUIPMENT



J5000™ Gun - with M22 swivel and extension.

Lance / Nozzle - Dual lance with variable pressure control complete with hardened nozzles.

Hose - 15m of 3/8" double wire braided hose with quick coupling(s).

OPTIONAL ACCESSORIES

Accessory	p/n	Included
High Pressure Swivel	p/n	Included
Additional High Pressure Hose (per metre)	p/n	52001
Complete Turbo Head with Lance	p/n	JWA160.04
LS12 Foaming Lance with Tank	p/n	JWA221-LS12
JW Pro Foam Bypass System	p/n	PROFOAM.04
OEM Hose Reel (30m Capacity)	p/n	1060Cmpl
Pro Rapid Style Hose Reel (60m Capacity)	p/n	1067Cmpl
Pro Rapid Stainless Steel Hose Reel (60m Capacity)	p/n	1067CmplSS
Hammerhead™ FSC 21" - ABS Plastic	p/n	JWA-FSC21.04
Hammerhead™ FSC 21" - Stainless Steel	p/n	JWA-FSC22.04
Giraffe™ Alloy Telescopic Lance	p/n	JWA-TELE7.3.04
Sandblasting Kit	p/n	JWA164
Sludge Kit	p/n	80005
Drain Cleaning Hose	p/n	HOP2X15VF
Professional Drain Cleaning Kit	p/n	JWA-PDCK
Vulcan V1 Hot Box	p/n	10199

MACHINE OPTIONALS

Accessory	p/n	Included
Emergency Stop, Battery Isolator, 4 Wheel Trolley Kit	p/n	Included
Engine Hour Meter	p/n	TOL8075
5L Stainless Steel Chemical Holder	p/n	CHEM-5L

Product Code	p/n	CW4000-15PG2
--------------	-----	--------------

TECHNICAL DATA

Working Pressure	psi / bar	4060 / 280
Flow Rate	l/pm	15
Max Water Inlet Temp	°c / °f	60 / 140
Class (AS/NZS: 4233)	grade	A (4,200 BAR/LITRES)

INTENDED APPLICATION

Usage Frequency	hours / type	4 Daily / Daily Usage
Category of Dirt / Debris	type	Medium

MOTOR FEATURES

Engine	type	HONDA™ GX390 (4 stroke, air cooled)
Power	hp / cc	13 / 390
Fuel Supply	type	Unleaded
Fuel Capacity	litres	6.1
Low Oil Shutdown	y / n	Y
Hour Meter	y / n	N
Starting System	type	Pull Start

HYDRAULIC FEATURES

Pump / Head / Pistons	type	JW® Italian Triplex Plunger/Brass (Nickel Plated)/Ceramic
Motor Pump Coupling	type	Gearbox Drive
Pump Speed	rpm	1450
Unloader Valve	type	Independent (Zero)
Safety Valve	y / n	Y
Orifice / Nozzle	size	04

OTHER FEATURES

Adjustable Pressure	y / n	Y
Hose Reel Provision	y / n	Y
Frame Structure	type	CNC Modular skid with heavy gauge galvanised steel chassis plus satin powder coat finish and stainless steel cover
Onboard Accessory Storage	y / n	Y
Detergent Injector	y / n	Y - Downstream low pressure adjustable

DIMENSIONS & WEIGHT

Approx Weight	kg	86 unit / 96 boxed
Unit Dimensions	mm	880(L) x 550(W) x 860(H)
Boxed Dimensions	mm	1200(L) x 800(W) x 1200(H)
Number per Pallet	type: pieces	Euro: 1

WARRANTY(S)

Engine Warranty*	year(s)	3 
Pump Warranty*	year(s)	2 

*Coverage against defects in material and workmanship (refer to Jetvac's and component partners T&Cs). The manufacturer reserves the right to modify design features and technical facts without notice, due to our principals of continuous improvement.